



ANTIFREEZE LIQUID

APPLICATIONS

ANTIFREEZE LIQUID is suitable for the cooling water systems such as diesel engines, internal combustion engines, car refrigerators, central heating, solar boilers e.t.c. and generally, where a low freezing point is requested.

DIRECTIONS FOR USE

ANTIFREEZE LIQUID is normally used neat and does not freeze at temperatures up to -15 °C.

When diluted with water the pour point rises.

Indicatively when diluted with water in a ratio 1:1 the pour point rises up to -6 °C.

NATURE OF SPECIAL RISKS AND SAFETY ADVICE

In accordance with the latest EEC Council directives this product is subjected to:

Signal word (CLP) : Warning

Hazardous ingredients: Ethanediol

Hazard statements (CLP): H302 - Harmful if swallowed

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (CLP): : P260 - Do not breathe dust/fumes/gas/mist/vapours/spray

P264 - Wash ... thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P301+P312 - IF SWALLOWED: Call a POISON CENTER/doctor/... if you feel unwell.

P314 - Get medical advice / attention if you feel unwell

P330 - Rinse mouth

Child-resistant fastening: NO

Tactile warning: NO

Code: 161162214

ANTIFREEZE LIQUID

Antifreeze Liquid is a special product, containing ethylene-glycol, sequestering agents and other anticorrosive compounds.

- Low pour point
- Provides the cooling water with Anti - corrosion properties.
- Prevents salt deposits.

PRODUCT CHARACTERISTICS

Appearance: clear blue liquid

Specific gravity: 1.05 ± 0.02

Flash point: None

Freezing Point: Less than - 15°C

pH: Higher than 8.

Solubility: Soluble in all proportions with water



This information is not to be taken as a warranty or representation for which we assume legal responsibility, nor as permission, inducement or recommendation to practice any patented invention without a licence. The information is offered solely for your consideration, investigation and verification.