



Code: 161161516

PET COKE CLEANER

Effective liquid product for
pet coke removal

PRODUCT CHARACTERISTICS

Colour: Red Liquid
Odor: Soft
Density at 20°C: 1.05 ± 0.05 g/cm³
Flash Point: None
pH (undiluted): 12.5 ± 1.0
Solubility: Soluble in water
Compatibility (concentrated):
Incompatible with aluminum, zinc, tin
and their alloys

PET COKE CLEANER

DESCRIPTION:

PET COKE CLEANER is a concentrated product, specially formulated to successfully remove pet coke from cargo and storage tanks. It contains special detergents and builders. It helps with cargo hold cleaning, by removing stains and discolouring after cargo discharge. PET COKE CLEANER is water based and non-flammable.

APPLICATION:

PET COKE CLEANER is mainly used in cargo and storage tanks but may also be used for the removal of mineral deposits in tanks and other closed systems. It can also be applied as a general purpose cleaner to eliminate bad odors in tanks and other closed systems.

PROPERTIES:

It is highly recommended to always test all cleaner solutions on a small area of tank coating, before full scale application.

STORAGE, HANDLING & DOSAGES

Instructions are based on experience and are meant only as a guide since circumstances for each tank cleaning operation vary. They are not intended to interfere with the judgment of the vessel's responsible personnel.

Always try to pre-clean tanks with high pressure water, so as to remove large deposits and ensure an effective cleaning operation. Be sure that the surface has dried, before applying the chemicals, in order to avoid unnecessary dilution of chemicals used.

PET COKE CLEANER may be used neat or diluted in water. Dose rates of PET COKE CLEANER vary depending on the degree of contamination, the type of surface to be cleaned, and the available downtime. For moderate contamination, use 50% solution in water. When the residues persist, or the contamination is heavy, PET COKE CLEANER may be used undiluted.

PET COKE CLEANER may be applied by conventional means like brushing, spray-ing or mopping. Leave product for about 30 minutes to act and then rinse thoroughly with high pressure water. If contamination persists, repeat the cleaning procedure, until the required result is obtained.



This information is not to be taken as a warranty or representation for which we assume legal responsibility, nor as permission, inducement or recommendation to practice any patented invention without a licence. The information is offered solely for your consideration, investigation and verification.