



UNICLEAN BREAK (Demulsifier)

DESCRIPTION:

UNICLEAN BREAK (Demulsifier) is a heavy-duty tank and bilge cleaner. It contains wetting agents, detergents and demulsifiers. The quick separating properties leave the water-phase with less than 15 PPM of oil, which meets IMO requirements.

APPLICATIONS:

UNICLEAN BREAK (Demulsifier) is used for cleaning and gas freeing of mineral oil tanks and for cleaning of tanks upgrading from black to white or grain.

It can also be used as a general cleaner in the engine room and especially for cleaning bilges.

DIRECTIONS FOR USE:

TANK WASHING MACHINE

UNICLEAN BREAK (Demulsifier) is injected into the wash-waterline, at a rate of 1 lt. per ton of wash-water, through the cleaning cycle. The washwater should be maintained between 65 - 80°C. It is important to keep the tank bottom well stripped for efficient removal of deposits.

DIRECT SPRAY

UNICLEAN BREAK is sprayed undiluted using a non-atomizing spray onto the surfaces to be cleaned. Allow a reaction time of 30 minutes to 2 hours, depending on the degree of soiling, to ensure full penetration and reaction. Wash down all surfaces with hot water of between 65 - 80°C and a pressure of at least 5.6 kg / cm².

Transfer wash-water to slop tank and allow settling and separating. Where an oil-water separator is installed, discharge from the bottom of the tank through the oil-water separator. This is the best method to meet IMO requirements.

For use as a demulsifying agent for separating oily water, add 1 lt. of product to 1000lt. of oily water. Mix thoroughly and allow solution to stand for 4 - 6 hours for separation to take place.

NATURE OF SPECIAL RISKS AND SAFETY ADVICE

In accordance with the latest EEC Council directives this product is subjected to:

R65 : Harmful; may cause lung-damage if swallowed

S2 : Keep out of reach of children

S23 : Do not breathe gas, fumes, vapor or spray

S24 : Avoid contact with skin

S62 : If swallowed do not induce vomiting; seek medical advice immediately and show the container or label

Code: 161164417

UNICLEAN BREAK (Demulsifier)

Quick separating tank and general cleaner.

- Oil and water emulsions break up quickly after cleaning
- Meets IMO requirements, less than 15 PPM of oil remains in the water-phase
- Heavy duty cleaner, suitable for removal of most mineral oils, fats and grease

PRODUCT CHARACTERISTICS

Appearance: clear amber liquid

Density: 0,8 (20°C)

Flash Point: >63°C

IMO Class: 9 / III

UN Number: 3082

ADR: 9.11c)



This information is not to be taken as a warranty or representation for which we assume legal responsibility, nor as permission, inducement or recommendation to practice any patented invention without a licence. The information is offered solely for your consideration, investigation and verification.