



REVERSE OSMOSIS WATER TREATMENT

OSMO DISINFECTANT

DESCRIPTION

OSMO DISINFECTANT is a liquid formulation based on sodium bisulfate used in different water treatment processes, and particularly in REVERSE OSMOSIS plants.

Continuous dosing of OSMO DISINFECTANT ahead of the high-pressure pump provides a reducing action of chlorine and disinfecting of the membranes. The use of OSMO DISINFECTANT is also extended to the flushing of the membranes when the system is in idle condition thus blocking bacteria growth.

MAIN USES

In water treatment: to reduce polluting metal ions (electroplating, tannerys, paper mills, etc.), as reducing agent and de-ion-izer in reverse osmosis plants.

RECOMMENDED APPLICATIONS

The product is applied by continuous dosing ahead of the highpressure pump at rate of 60 PPM. It is not necessary to dilute the product, which is ready to use as is

Chlorine residual can be measured by using a CHLORINE TEST KIT.

Code: 161162314

OSMO DISINFECTANT
DISINFECTANT OF
R.O.MEMBRANES

PRODUCT CHARACTERISTICS:

Color: light yellow
Solubility in water: complete
Density: 1.34 kg/dm³
Flash point: none

Dangerous reaction: OSMO DISINFECTANT is stable at ambient temperature.
At temperatures close to its boiling point (approx. 104°C) it reacts violently with oxidizing products and with acids.



This information is not to be taken as a warranty or representation for which we assume legal responsibility, nor as permission, inducement or recommendation to practice any patented invention without a licence. The information is offered solely for your consideration, investigation and verification.